

# HE-VA Triple Tiller



Durox point - Reversible with 2 stage adjustment for longer life



**Effective  
Tined Cultivation**



# Extreme cultivation for all conditions

With working widths of 3m, 3.5m, 4m and 5m there is a Triple Tiller to suit the tractor you have.

The Triple Tiller is a high speed stubble cultivator designed to work down to 300mm (12") deep depending on conditions and the point option used.

The machine can be used with wide duckfoot shares fitted to cultivate shallow, moving all the ground in a mintill or stale seed-bed situation. With its chisel point fitted it can just as easily be used for deep cultivation and residue incorporation. The leveling tines and V-Profile roller fitted to the back of the Triple Tiller ensure that whichever use the machine is put to a level consolidated finish is left.

Machines come as standard with 75mm x 12mm reversible and height adjustable "Durox" hard wearing points, leveling tines and lights.



## Technical Specifications

| Model No.  | Working Width            | No. of Tines | Tractor HP   | Weight  |
|------------|--------------------------|--------------|--------------|---------|
| 10450-3060 | 3m - Three Point Mounted | 12           | 100 - 200 hp | 2470 kg |
| 10451-3060 | 3m - Trailed             | 12           | 100 - 200 hp | 3100 kg |
| 10451-4060 | 4m - Trailed             | 16           | 140 - 250 hp | 4500 kg |
| 10451-5060 | 5m - Trailed             | 20           | 160 - 280 hp | 5280 kg |

## Options

Quick change adapter with points 1 set of duckfoot and chisel points in lieu

Levelling discs in lieu of tines

Variocast seeder mounting kit

Trailed machines fitted with pivoting towing eye Ø50mm - 66630757017 see page 22 of the price list for options



CHERRY HOLT ROAD, BOURNE, LINCOLNSHIRE. PE10 9LG

TEL 01778 421111 • FAX 01778 425080

EMAIL ASK@OPICO.CO.UK

WEB WWW.OPICO.CO.UK/HE-VA

