

# Top Cutter Solo


Roll, cut and bruise cover, catch & vegetable crops



The twin rotor Top Cutter Solo is available in five widths:  
rigid in 3.00m, 3.50m 4.00m  
hydraulic folding in 4.00m, 5.00m and 6.00m



**HE-VA**

Distributed by 



# Mechanical Destruction

Aimed at both conventional and organic farmers, HE-VA's Top Cutter Solo is the stand-alone version of HE-VA's Top Cutter range of integrated vegetation and stubble control machines.

The twin rollers are designed to roll, cut and bruise cover, catch and vegetable crops in a form of mechanical destruction, thus reducing the reliance on herbicides and speeds up decomposition. Maize stubbles also benefit from this process by reducing the burden of the maize boring worm and fusarium, helping to reduce reliance on pesticides.

The standard twin rotor machine is front mounted, although it can be supplied with an optional 3-point kit to mount it on the rear of the tractor. Being front or rear mounted, it can be used independently or in conjunction with a cultivator or drill.

HE-VA Product Manager, Glenn Bootman, observed, "When the Top Cutter Solo is front mounted and is being used in conjunction with a rear mounted machine, it has the benefit of lying down the crop in the direction of travel to assist the working of the following machine.

As we all know, one pass systems have the economic benefit of time and fuel savings, as well as minimising compaction with reduced traffic, helping to conserve the integrity of the soil."

A strong robust headstock and main frame holds the rotors in place and each rotor is mounted on rubber suspended arms to reduce shock loading and increase longevity.

The individual rotors are 400mm in diameter, each with 6 blades mounted in a spiral formation to give a smooth, even rolling radius. The inherent rotary action means a low hp requirement is needed.

The rotors are covered by a robust steel canopy for safety protection as well as for reducing potential crop residue or soil from being thrown onto the tractor.


## OPTIONAL EXTRAS

- Rear 3-point linkage kit
- Marker lights
- Support wheels
- 30kg weight blocks
- Soil mat

## TOP CUTTER SOLO SPECIFICATIONS

Model	Working Width	Rotor	Type	Weight
1067055-10	3m	Twin	Rigid	990kg
1067055-20	3.5m	Twin	Rigid	1043kg
1067055-30	4m	Twin	Rigid	1180kg
1067055-45	4m	Twin	Folding	1620kg
1067055-55	5m	Twin	Folding	1810kg
1067055-65	6m	Twin	Folding	2050kg



Distributed by 

OPICO Ltd.  
Cherry Holt Road, Bourne,  
Lincolnshire PE10 9LA.  
01778 421111  
ask@opico.co.uk  
www.opico.co.uk  
@opicoag

YOUR LOCAL HE-VA DEALER