

HE-VA Combi-Lift Pre-cultivator

Lift your soil to lift your yields



HE-VA
distributed by 



The Combi-Lift Pre-Cultivator fits directly to the tractor linkage and incorporates a rear clevis which can be used to pull a cultivator or drill. Furthermore, the machine can also be fitted with low-disturbance legs to enable light loosening of compaction without heave in mintill or direct drilling situations.

The Combi-Lift comes in 3m (5 leg), 4m (7 or 8 leg) and 6m (11 or 12 leg) models, the hydraulic folding machines folding down to 2.5m transport width.

All models can be supplied with either "Hammer-Thru" multi-segmented shearbolt or automatic hydraulic reset leg protection.

FEATURES



SUBSOILING DEPTH

Maximum working depth of 350mm (14") enabling them to alleviate most types of soil pan and compaction.



SHEARBOLT

The Hammer-Thru shearbolt reduces the need to carry shearbolts, simply pull out the holding pin and push a segment through.



HYDRAULIC RESET

Allows the legs to trip back when they hit an obstacle and then reset automatically on the move.



CAST POINTS

Special cast iron points are available in 80mm, 120mm, 200mm (standard) widths.



REAR HD CLEVIS

A heavy duty rear clevis ensures heavy machines like drills can be pulled behind the Combi-Lift.

COMBI-LIFT SPECIFICATIONS

Model	Working Width	Transport Width	Protection	No. of Legs	Weight Kg	Max Hp
1064531-01	3m	3m	Shearbolt	5	890	350
1064531-11	3m	3m	Hydraulic Reset	5	1035	350
1064531-86	4m	2.5m	Shearbolt	7/8	1310/1395	350
1064531-87	4m	2.5m	Hydraulic Reset	7/8	1450/1670	350
1064531-92	6m	2.5m	Shearbolt	11/12	2130/2250	500
1064531-93	6m	2.5m	Hydraulic Reset	11/12	2265/2385	500



distributed by OPICO

Cherry Holt Road, Bourne,
Lincolnshire, PE10 9LA
Tel: 01778 421111
Fax: 01778 425080
Email: ask@opico.co.uk
Web: www.he-va.co.uk

Due to our company policy of continual improvement we reserve the right to change specifications and/or prices without prior notification.